



中国认可  
国际互认  
检测  
TESTING  
CNAS L094

# SPECIAL EQUIPMENT TYPE-EXAMINATION CERTIFICATE ( Elevator )

Certificate No. TSX F31003720180073

**Applicant Name:** Guangdong Huahui Elevator Accessories Co., Ltd.

**Applicant address:** West of Gangkou Road, Dongqu Sanshan, Guicheng Street, Nanhai District, Foshan City, Guangdong Province, P.R. China

**Manufacturer name:** Guangdong Huahui Elevator Accessories Co., Ltd.

**Manufacturer address:** West of Gangkou Road, Dongqu Sanshan, Guicheng Street, Nanhai District, Foshan City, Guangdong Province, P.R. China

**Equipment type:** Lift Safety Protection Device      **Equipment kind:** Overspeed governor

**Product name:** Overspeed governor      **Product type:** XSG607-B15

Inspection report No. TSX F310T3720180073

By the Type-Examination, the prototype (product) is confirmed to be in accordance with Regulation for Type Tests of Elevators (TSG T7007-2016), GB 7588-2003 Safety Rules for the Construction and Installation of Electric Lifts (Including 1<sup>st</sup> Revision List), EN81-20:2014 and EN81-50:2014.

Applicable product type of the certificate: XSG607-B15

Applicable product parameter range and configuration is to see the annex.

(Stamp)

Issue date: 2018/07/07

Date of replacement: /

Date of next inspection: Before 2020/07/07



**Guangdong Institute of Special Equipments Inspection and Research  
National Elevator Quality Supervision and Inspection Center  
( Guangdong )**

- Note 1: Applicant has the responsibility to ensure that products comply with the provisions of the safety technical norms and standards, and the consistency with experimental testing prototype (sample).
- Note 2: This certificate shall not apply to the products manufactured after the next check date.
- Note 3: The elevator standards involved in this certificate has been accepted by CNAS laboratory, and TSG T7007-2016 is temporarily not within the scope of CNAS accept recognition.



### Product Technical Parameters and Configuration Table

|  |   |  |  |                   |
|--|---|--|--|-------------------|
| <b>Rated Speed</b>   |   | 1.5m/s   | <b>Structure Pattern</b>                 | Centrifugal block |
| <b>Structure for tension force generation</b>                    |   | Clamping type  | <b>Rope Sheave Pitch Circle Diameter</b> | 240mm             |
| <b>Wire rope Diameter</b>  |   | 8mm  | <b>Rope Race Type</b>                    | U groove          |
| <b>Rope Tension Force</b>  |   | /  | <b>Pulling Force</b>                     | ≥1200N            |
| <b>Mechanical Trigering Device</b>                               | <b>Tripping downward safety gears of car or counterweight</b> |  |  | Applicable        |
|  | <b>Tripping wire rope brake</b>                               |  |  | Not applicable    |
|  | <b>Tripping upward safety gears</b>                           |  |  | Not applicable    |
|  | <b>Tripping other type of brake unit for ACOP</b>             |  |  | Not applicable    |
| <b>Electric Security Protector&amp; Electric Tripping Device</b> | <b>Electric device on overspeed checking</b>                  |  |  | Applicable        |
|  | <b>Electric device on reset checking</b>                      |  |  | Applicable        |
|  | <b>Active device of ACOP</b>                                  | <b>Active brakes on drive machine</b>                    |  | Applicable        |
|  |   | <b>Active brake unit on wire rope or traction sheave</b> |  | Not applicable    |
|  |   | <b>Active brake unit of other type</b>                   |  | Not applicable    |
| <b>Remote control function</b>                                   |   | Not configured   | <b>Working condition</b>                 | Indoors           |
| <b>Explosion-proof type</b>                                      |   | /  |  |                   |